

Ø Inches	Description	CAI MSPN	Tyre characteristics				Rims	Tube	75% Internal volume	Tread depth	Pressure bar and psi - Load per tire in lbs																		
			S	D	R'	C.d.R.					pouces inches	litres Gals	mm 32nd	Bar Psi	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
			mm inches	mm inches	mm inches	mm inches									17	20	23	25	26	28	29	30	32	33	35	36	38	39	41
26	VF 520/80 R26 CFO+ 168A8 TL CEREXBIB 2	850494	503	1,491	649	4,400	DW16L	716	366	44	6 mph Cyc	11 530	12 800	14 055	14 350	14 650	14 935	15 235	15 530	15 820	16 115	16 400	16 755	17 110	17 450	17 800			
		24394	20	58	25.6	173.2	DW18L W16L		96.7	55/32nd	10 mph Cyc	10 505	11 660	12 820	13 085	13 360	13 625	13 890	14 155	14 420	14 685	14 945	15 265	15 600	15 915	16 235			
		228272	606	1,513	655	4,461	DW20B (A)		462.75	45	25 mph	7 825	8 740	9 645	9 855	10 075	10 285	10 495	10 715	10 925	11 145	11 355	11 605	11 850	12 105	12 345			
	VF 620/70 R26 CFO+ 173A8 TL CEREXBIB 2	98039	24	59	25.8	175.6	DW20B (A)	716	122.2	57/32nd	6 mph Cyc	13 305	14 860	16 400	16 765	17 130	17 495	17 855	18 220	18 585	18 940	19 300	19 720	20 150	20 570	20 990			
		132266	748	1,623	701	4,786	DW25B (A)	833	659.25	48	10 mph Cyc	12 135	13 545	14 945	15 280	15 610	15 940	16 270	16 600	16 945	17 275	17 605	17 990	18 370	18 750	19 135			
		33777	29	64	27.6	188.4	DW25B (A)	833	174.1	60/32nd	25 mph	9 095	10 230	11 355	11 585	11 830	12 060	12 290	12 520	12 755	12 995	13 230	13 505	13 780	14 055	14 330			
30	VF 520/85 R30 CFO+ 172A8 TL CEREXBIB 2	188276	522	1,624	709	4,797	W16L	737	435	46	6 mph Cyc	12 930	14 430	15 930	16 225	16 525	16 810	17 110	17 405	17 690	17 990	18 275	18 815	19 355	19 885	20 425			
		86907	21	64	27.9	188.9	W16L		737	114.9	58/32nd	10 mph Cyc	11 795	13 160	14 530	14 795	15 060	15 320	15 585	15 850	16 125	16 390	16 655	17 150	17 650	18 135	18 630		
		049288	608	1,615	700	4,765	DW20B (A)		737	505.5	43	25 mph	8 820	9 790	10 750	11 000	11 265	11 520	11 775	12 025	12 280	12 535	12 785	13 060	13 340	13 615	13 890		
	VF 620/70 R30 CFO+ 175A8 TL CEREXBIB 2	53106	24	63	27.6	187.6	DW20B (A)	737	133.5	54/32nd	6 mph Cyc	14 055	15 695	17 340	17 725	18 110	18 495	18 885	19 270	19 655	20 040	20 425	20 945	21 340	21 970	22 485			
		608814	693.9	1,676	735	4,952	DW25B (A)	833	630	46	10 mph Cyc	12 820	14 320	15 805	16 160	16 515	16 865	17 220	17 570	17 925	18 275	18 630	19 105	19 565	20 040	20 505			
		22560	27	66	28.9	195	DW23B (A)	833	166.4	58/32nd	25 mph	9 920	10 970	12 015	12 245	12 490	12 720	12 950	13 185	13 425	13 660	13 890	14 220	14 550	14 880	15 210			
32	IF 800/65 R32 CFO+ 181A8 TL CEREXBIB2	987406	772	1,855	826	5,501	DW27B (A)	831	903	57	6 mph Cyc	19 865	21 740	23 610	24 175	24 735	25 300	25 860	26 420	26 985	27 545	28 110	28 815	29 520	30 215	30 920			
		25367	30	73	32.5	216.6	DW27B (A)		831	238.5	72/32nd	10 mph Cyc	18 110	19 820	21 530	22 045	22 555	23 070	23 580	24 095	24 605	25 120	25 630	26 270	26 920	27 560	28 195		
		789156	796	1,950	864	5,800	DW27B (A)		831	966	55	25 mph	11 685	12 785	13 890	14 220	14 550	14 880	15 210	15 545	15 875	16 205	16 535	16 955	17 360	17 780	18 190		
	IF 800/70 R32 CFO+ 185A8 TL CEREXBIB2	71535	31	76	34	228.3	DW27B (A)	831	255.1	69/32nd	6 mph Cyc	21 740	24 175	26 610	27 270	27 920	28 585	29 235	29 895	30 545	31 205	31 855	32 560	33 270	33 960	34 670			
		430737	856	1,906	827	5,618	DW27B (A)	831	1,032.75	58	10 mph Cyc	19 820	22 045	24 260	24 855	25 465	26 060	26 655	27 250	27 855	28 450	29 045	29 685	30 335	30 975	31 615			
		73624	34	75	32.6	221.2	DW30B (A)	831	272.8	73/32nd	25 mph	12 785	14 220	15 655	16 040	16 425	16 810	17 195	17 580	17 970	18 355	18 740	19 160	19 565	19 985	20 395			
34	VF 500/85 R34 CFO+ 172A8 TL CEREXBIB2	038009	497	1,676	741	4,961	DW16L	831	430.5	46	6 mph Cyc	12 940	14 210	15 475	15 830	16 180	16 525	16 875	17 230	17 580	17 925	18 275	18 675	19 070	19 465	19 865			
		29877	20	66	29.2	195.3	DW18L		831	113.7	58/32nd	10 mph Cyc	11 795	12 950	14 110	14 430	14 750	15 070	15 390	15 710	16 030	16 345	16 665	17 030	17 395	17 760	18 120		
		953912	646	2,020	904	6,030	DW21B		804	876.75	59	25 mph	8 820	9 790	10 750	10 945	11 155	11 355	11 550	11 750	11 950	12 145	12 345	12 730	13 120	13 505	13 890		
	IF 680/80 R38 CFO+ 182A8 TL CEREXBIB2	20691	25	79	35.6	237.4	DW21B	804	231.6	74/32nd	6 mph Cyc	20 425	22 775	25 110	25 605	26 090	26 590	27 085	27 570	28 065	28 550	29 045	29 750	30 455	31 150	31 855			
		610997	790	2,051	912	6,079	DW27B (A)	804	1,087.5	57	10 mph Cyc	18 630	20 770	22 895	23 345	23 800	24 240	24 690	25 145	25 595	26 035	26 490	27 130	27 765	28 405	29 045			
		439024	879	2,029	889	5,993	DW30B (A)	804	1,149	58	25 mph	12 015	13 395	14 770	15 060	15 355	15 640	15 930	16 215	16 515	16 800	17 085	17 505	17 915	18 330	18 740			
42	VF 520/85 R42 CFO+ 177A8 TL CEREXBIB 2	270459	541	1,953	881	5,807	DW18B(A)	802	544.5	55	6 mph Cyc	13 195	14 640	16 085	16 470	16 845	17 230	17 605	17 990	18 365	18 750	19 125	19 545	19 950	20 370	20 780			
		15337	21	77	34.7	228.6	DD18 W18L		802	143.8	69/32nd	10 mph Cyc	12 025	13 350	14 660	15 015	15 355	15 710	16 050	16 400	16 745	17 090	17 440	17 815	18 200	18 575	18 950		
		844076	580	2,040	903	6,040	DW18B(A)		802	700.5	58	25 mph	10 195	11 495	12 785	13 040	13 285	13 535	13 780	14 030	14 275	14 530	14 770	15 100	15 430	15 765	16 095		
	VF 580/85 R42 CFO+ 183A8 TL CEREXBIB2	45547	23	80	35.6	237.8	DW18B(A)	802	185	73/32nd	6 mph Cyc	17 800	19 775	21 740	22 155	22 585	23 005	23 425	23 845	24 275	24 690	25 110	25 860	26 610	27 360	28 110			
		499992	705	2,097	927	6,207	DW23B (A)	802	867	64	10 mph Cyc	16 235	18 035	19 820	20 205	20 590	20 975	21 365	21 740	22 125	22 510	22 895	23 580	24 260	24 945	25 630			
		818789	770	2,118	964	6,387	DW27B (A)	802	1,144.5	58	25 mph	15 675	17 405	19 135	19 510	19 875	20 250	20 615	20 990	21 350	21 725	22 090	22 750	23 415	24 075	24 735			
IF 800/70 R42 CFO+ 189A8 TL CEREXBIB2	91180	30	83	38	251.5	DW25B (A)	802	302.3	73/32nd	6 mph Cyc	14 285	15 860	17 440	17 780	18 120	18 455	18 795	19 135	19 480	19 810	20 150	20 755	21 350	21 970	22 555				
	856296	843	2,118	930	6,281	DW28B (A)	802	1,227	59	10 mph Cyc	13 890	15 485	17 085	17 430	17 780	18 120	18 465	18 805	19 160	19 500	19 840	20 260	20 670	21 085	21 495				
	03717	33	83	36.6	247.3	DW30B (A)	802	324.1	74/32nd	25 mph	20 425	22 775	25 110	25 605	26 090	26 590	27 075	27 570	28 065	28 550	29 045	29 750	30 455	31 150	31 855				
VF 900/60 R42 CFO+ 195A8 TL CEREXBIB2	856296	843	2,118	930	6,281	DW30B (A)	802	1,227	59	6 mph Cyc	18 630	20 770	22 895	23 345	23 800	24 240	24 690	25 145	25 595	26 035	26 490	27 130	27 765	28 405	29 045				
	03717	33	83	36.6	247.3	TW30B	802	324.1	74/32nd	10 mph Cyc	22 210	24 780	27 335	27 975	28 615	29 255	29 905	30 545	31 185	31 825	32 465	33 145	33 830	34 515	35 195				
	03717	33	83	36.6	247.3	TW30B	802	324.1	74/32nd	25 mph	14 330	15 985	17 635	18 055	18 465	18 885	19 290	19 710	20 115	20 535	20 945	21 385	21 825	22 265	22 710				
VF 900/60 R42 CFO+ 195A8 TL CEREXBIB2	856296	843	2,118	930	6,281	DW30B (A)	802	1,227	59	6 mph Cyc	28 110	31 395	34 670	35 585	36 500	37 410	38 325	39 230	40 145	41 060	41 975	42 870	43 760	44 645	45 535				
	03717	33	83	36.6	247.3	TW30B	802	324.1	74/32nd	10 mph Cyc	25 630	28 625	31 615	32 450	33 280	34 115	34 945	35 780	36 610	37 445	38 270	39 090	39 905	40 710	41 525				
	03717	33	83	36.6	247.3	TW30B	802	324.1	74/32nd	25 mph	16 535	18 465	20 395	20 935	21 475	22 000	22 540	23 080	23 625	24 150	24 690	25 220	25 740	26 270	26 785				