

# MICHELIN AGRIBIB Row Crop

Traction



Service Life



## ■ Excellent traction and lateral stability

- Robust crown
- Deep tread bars

## ■ Service life

- Deep R1W lug design for a long tread life

### ■ Deep tread bars

- Excellent traction



### ■ Robust crown

- Good lateral stability

## Sizes

320/85 R38 TL 143A8/143B  
320/90 R42 TL 147A8/147B  
340/85 R46 TL 150A8/150B

380/90 R46 TL 157A8/157B  
320/90 R50 TL 150A8/150B

380/90 R50 TL 151A8/151B  
320/90 R54 TL 151A8/151B

# MICHELIN AGRIBIB Row Crop

## 320/85 R38 143A8/143B TL AGRIBIB RC

MSPN: 50528

CAI: 758001

Load per tire (single)							Tire Technical Data				
30 mph 50 km/h	20 mph 30 km/h	15 mph 25 km/h	20 mph Cyc 30 km/h Cyc	15 mph Cyc 25 km/h Cyc	6 mph Cyc 10 km/h Cyc	Pressure	Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold) <b>W10</b> DW10A, W11, DW11A
							Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	
3,420 lbs	3,660 lbs	3,790 lbs	3,900 lbs	4,170 lbs		17 psi	12.4 in	59.4 in	27.5 in	177.7 in	DW10A, W11, DW11A
1,550 kgs	1,660 kgs	1,720 kgs	1,770 kgs	1,890 kgs		1.2 bar	315 mm	1,508 mm	699 mm	4,514 mm	
4,080 lbs	4,370 lbs	4,520 lbs	4,650 lbs	4,980 lbs	5,140 lbs	23 psi	Rolling Circumference Index 42				Tube MSPN
1,850 kgs	1,980 kgs	2,050 kgs	2,110 kgs	2,260 kgs	2,330 kgs	1.6 bar					
4,440 lbs	4,750 lbs	4,930 lbs	5,070 lbs	5,420 lbs	5,970 lbs	29 psi	Number of Lugs 30 x 2				Tube CAI BFG039240
2,015 kgs	2,155 kgs	2,235 kgs	2,300 kgs	2,460 kgs	2,710 kgs	2.0 bar					
4,810 lbs	5,140 lbs	5,340 lbs	5,490 lbs	5,860 lbs	6,810 lbs	35 psi	Gross Flat Plate				Minimum Dual/Triple Spacing
2,180 kgs	2,330 kgs	2,420 kgs	2,490 kgs	2,660 kgs	3,090 kgs	2.4 bar					
5,250 lbs	5,610 lbs	5,820 lbs	5,990 lbs	6,390 lbs	7,310 lbs	41 psi	Tire Weight				17.1 in
2,380 kgs	2,545 kgs	2,640 kgs	2,715 kgs	2,900 kgs	3,315 kgs	2.8 bar					
5,680 lbs	6,080 lbs	6,310 lbs	6,480 lbs	6,920 lbs	7,800 lbs	46 psi	100% Tire Volume				434 mm
2,575 kgs	2,760 kgs	2,860 kgs	2,940 kgs	3,140 kgs	3,540 kgs	3.2 bar					
5,840 lbs	6,260 lbs	6,480 lbs	6,670 lbs	7,120 lbs	8,160 lbs	49 psi	Centerline Tread Depth				
2,650 kgs	2,840 kgs	2,940 kgs	3,025 kgs	3,230 kgs	3,700 kgs	3.4 bar					
6,010 lbs	6,440 lbs	6,660 lbs	6,860 lbs	7,320 lbs	8,510 lbs	52 psi	83 kgs				
2,725 kgs	2,920 kgs	3,020 kgs	3,110 kgs	3,320 kgs	3,860 kgs	3.6 bar					
					8,760 lbs	55 psi	42 mm				
					3,975 kgs	3.8 bar					
					9,020 lbs	58 psi	4.0 bar				
					4,090 kgs	4.0 bar					

\*All load values are for maximum indicated speeds at low torque.  
**\*20 mph (30 km/h): high torque field work or max road speed.**  
 \*All load values for ground slopes up to 20% (above 20% consult Michelin)

## 320/90 R42 147A8/147B TL AGRIBIB RC

MSPN: 64720

CAI: 425361

Load per tire (single)							Tire Technical Data				
30 mph 50 km/h	20 mph 30 km/h	15 mph 25 km/h	20 mph Cyc 30 km/h Cyc	15 mph Cyc 25 km/h Cyc	6 mph Cyc 10 km/h Cyc	Pressure	Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold) <b>DW10L</b> W10L, W9L
							Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	
3,750 lbs	4,010 lbs	4,170 lbs	4,280 lbs	4,570 lbs		17 psi	12.3 in	64.5 in	30.1 in	193.2 in	DW10L W10L, W9L
1,700 kgs	1,820 kgs	1,890 kgs	1,940 kgs	2,075 kgs		1.2 bar	312 mm	1,638 mm	764 mm	4,908 mm	
4,540 lbs	4,850 lbs	5,050 lbs	5,530 lbs	5,530 lbs	6,280 lbs	23 psi	Rolling Circumference Index 44				Tube MSPN
2,060 kgs	2,200 kgs	2,290 kgs	2,510 kgs	2,510 kgs	2,850 kgs	1.6 bar					
4,950 lbs	5,290 lbs	5,500 lbs	5,820 lbs	6,040 lbs	7,040 lbs	29 psi	Number of Lugs 30 x 2				Tube CAI
2,245 kgs	2,400 kgs	2,495 kgs	2,640 kgs	2,740 kgs	3,195 kgs	2.0 bar					
5,360 lbs	5,730 lbs	5,950 lbs	6,110 lbs	6,540 lbs	7,800 lbs	35 psi	Gross Flat Plate				Minimum Dual/Triple Spacing
2,430 kgs	2,600 kgs	2,700 kgs	2,770 kgs	2,965 kgs	3,540 kgs	2.4 bar					
5,880 lbs	6,280 lbs	6,530 lbs	6,700 lbs	7,170 lbs	8,290 lbs	41 psi	Tire Weight				17.1 in
2,665 kgs	2,850 kgs	2,960 kgs	3,040 kgs	3,250 kgs	3,760 kgs	2.8 bar					
6,390 lbs	6,830 lbs	7,100 lbs	7,290 lbs	7,800 lbs	8,760 lbs	46 psi	100% Tire Volume				434 mm
2,900 kgs	3,100 kgs	3,220 kgs	3,305 kgs	3,540 kgs	3,975 kgs	3.2 bar					
6,590 lbs	7,040 lbs	7,320 lbs	7,510 lbs	8,040 lbs	9,170 lbs	49 psi	Centerline Tread Depth				
2,990 kgs	3,195 kgs	3,320 kgs	3,405 kgs	3,645 kgs	4,160 kgs	3.4 bar					
6,780 lbs	7,250 lbs	7,530 lbs	7,730 lbs	8,270 lbs	9,590 lbs	52 psi	212 lbs				
3,075 kgs	3,290 kgs	3,415 kgs	3,505 kgs	3,750 kgs	4,350 kgs	3.6 bar					
					9,880 lbs	55 psi	42 mm				
					4,480 kgs	3.8 bar					
					10,160 lbs	58 psi	4.0 bar				
					4,610 kgs	4.0 bar					

\*All load values are for maximum indicated speeds at low torque.  
**\*20 mph (30 km/h): high torque field work or max road speed.**  
 \*All load values for ground slopes up to 20% (above 20% consult Michelin)

NOTE:

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%





### 340/85 R46 150A8/150B TL AGRIBIB RC

MSPN: 94547

CAI: 846786

Load per tire (single)						
30 mph 50 km/h	20 mph 30 km/h	15 mph 25 km/h	20 mph Cyc 30 km/h Cyc	15 mph Cyc 25 km/h Cyc	6 mph Cyc 10 km/h Cyc	Pressure
4,080 lbs	4,370 lbs	4,520 lbs	4,650 lbs	4,980 lbs		17 psi
1,850 kgs	1,980 kgs	2,050 kgs	2,110 kgs	2,260 kgs		1.2 bar
4,940 lbs	5,290 lbs	5,490 lbs	5,620 lbs	6,020 lbs	6,130 lbs	23 psi
2,240 kgs	2,400 kgs	2,490 kgs	2,550 kgs	2,730 kgs	2,780 kgs	1.6 bar
5,390 lbs	5,780 lbs	5,990 lbs	6,140 lbs	6,570 lbs	7,200 lbs	29 psi
2,445 kgs	2,620 kgs	2,715 kgs	2,785 kgs	2,980 kgs	3,265 kgs	2.0 bar
5,840 lbs	6,260 lbs	6,480 lbs	6,660 lbs	7,120 lbs	8,270 lbs	35 psi
2,650 kgs	2,840 kgs	2,940 kgs	3,020 kgs	3,230 kgs	3,750 kgs	2.4 bar
6,390 lbs	6,850 lbs	7,100 lbs	7,290 lbs	7,790 lbs	8,930 lbs	41 psi
2,900 kgs	3,105 kgs	3,220 kgs	3,305 kgs	3,535 kgs	4,050 kgs	2.8 bar
6,940 lbs	7,430 lbs	7,720 lbs	7,910 lbs	8,470 lbs	9,590 lbs	46 psi
3,150 kgs	3,370 kgs	3,500 kgs	3,590 kgs	3,840 kgs	4,350 kgs	3.2 bar
7,170 lbs	7,660 lbs	7,960 lbs	8,170 lbs	8,740 lbs	10,010 lbs	49 psi
3,250 kgs	3,475 kgs	3,610 kgs	3,705 kgs	3,965 kgs	4,540 kgs	3.4 bar
7,390 lbs	7,890 lbs	8,200 lbs	8,420 lbs	9,020 lbs	10,430 lbs	52 psi
3,350 kgs	3,580 kgs	3,720 kgs	3,820 kgs	4,090 kgs	4,730 kgs	3.6 bar
					10,760 lbs	55 psi
					4,880 kgs	3.8 bar
					11,090 lbs	58 psi
					5,030 kgs	4.0 bar

\*All load values are for maximum indicated speeds at low torque.  
**\*20 mph (30 km/h): high torque field work or max road speed.**  
 \*All load values for ground slopes up to 20% (above 20% consult Michelin)

Tire Technical Data								
Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)				
Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference					
13.3 in	68.8 in	31.9 in	205.8 in	<b>W12</b> W10, DW10A, W12A				
338 mm	1,747 mm	810 mm	5,227 mm					
<table border="1"> <tr><td>Rolling Circumference Index</td></tr> <tr><td>45</td></tr> <tr><td>Number of Lugs</td></tr> <tr><td>33 x 2</td></tr> </table>				Rolling Circumference Index	45	Number of Lugs	33 x 2	Tube MSPN
Rolling Circumference Index								
45								
Number of Lugs								
33 x 2								
				Tube CAI TL				
				Minimum Dual/Triple Spacing				
Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth					
212 sq in	225 lbs	79.2 gals	52/32nd	18.2 in				
1,367 sq cm	102 kgs	300 liters	41 mm	462 mm				

### 380/90 R46 157A8/157B TL AGRIBIB RC

MSPN: 38865

CAI: 799905

Load per tire (single)						
30 mph 50 km/h	20 mph 30 km/h	15 mph 25 km/h	20 mph Cyc 30 km/h Cyc	15 mph Cyc 25 km/h Cyc	6 mph Cyc 10 km/h Cyc	Pressure
5,070 lbs	5,420 lbs	5,620 lbs	5,780 lbs	6,190 lbs		17 psi
2,300 kgs	2,460 kgs	2,550 kgs	2,620 kgs	2,810 kgs		1.2 bar
6,170 lbs	6,610 lbs	6,860 lbs	7,030 lbs	7,540 lbs	7,610 lbs	23 psi
2,800 kgs	3,000 kgs	3,110 kgs	3,190 kgs	3,420 kgs	3,450 kgs	1.6 bar
6,670 lbs	7,140 lbs	7,410 lbs	7,610 lbs	8,150 lbs	8,880 lbs	29 psi
3,025 kgs	3,240 kgs	3,360 kgs	3,450 kgs	3,695 kgs	4,030 kgs	2.0 bar
7,170 lbs	7,670 lbs	7,960 lbs	8,180 lbs	8,750 lbs	10,160 lbs	35 psi
3,250 kgs	3,480 kgs	3,610 kgs	3,710 kgs	3,970 kgs	4,610 kgs	2.4 bar
7,850 lbs	8,410 lbs	8,720 lbs	8,960 lbs	9,590 lbs	10,960 lbs	41 psi
3,560 kgs	3,815 kgs	3,955 kgs	4,065 kgs	4,350 kgs	4,970 kgs	2.8 bar
8,540 lbs	9,150 lbs	9,480 lbs	9,740 lbs	10,430 lbs	11,750 lbs	46 psi
3,875 kgs	4,150 kgs	4,300 kgs	4,420 kgs	4,730 kgs	5,330 kgs	3.2 bar
8,820 lbs	9,440 lbs	9,790 lbs	10,050 lbs	10,760 lbs	12,280 lbs	49 psi
4,000 kgs	4,280 kgs	4,440 kgs	4,560 kgs	4,880 kgs	5,570 kgs	3.4 bar
9,090 lbs	9,720 lbs	10,100 lbs	10,360 lbs	11,090 lbs	12,810 lbs	52 psi
4,125 kgs	4,410 kgs	4,580 kgs	4,700 kgs	5,030 kgs	5,810 kgs	3.6 bar
					13,230 lbs	55 psi
					6,000 kgs	3.8 bar
					13,650 lbs	58 psi
					6,190 kgs	4.0 bar

\*All load values are for maximum indicated speeds at low torque.  
**\*20 mph (30 km/h): high torque field work or max road speed.**  
 \*All load values for ground slopes up to 20% (above 20% consult Michelin)

Tire Technical Data								
Unloaded Dimensions		Loaded Dimensions		Rims (preferred in bold)				
Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference					
15.8 in	73.4 in	34.1 in	219.8 in	<b>W13A</b> W12A, DW13A, W13, DW13, W12				
401 mm	1,864 mm	867 mm	5,583 mm					
<table border="1"> <tr><td>Rolling Circumference Index</td></tr> <tr><td>46</td></tr> <tr><td>Number of Lugs</td></tr> <tr><td>34 x 2</td></tr> </table>				Rolling Circumference Index	46	Number of Lugs	34 x 2	Tube MSPN 31525
Rolling Circumference Index								
46								
Number of Lugs								
34 x 2								
				Tube CAI 203376				
				Minimum Dual/Triple Spacing				
Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth					
254 sq in	293 lbs	108.6 gals	58/32nd	20.4 in				
1,641 sq cm	133 kgs	411 liters	46 mm	519 mm				

NOTE:

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%



# MICHELIN AGRIBIB Row Crop

## 320/90 R50 150A8/150B TL AGRIBIB RC

MSPN: 95098

CAI: 130813

Load per tire (single)							Pressure	Tire Technical Data			
30 mph 50 km/h	20 mph 30 km/h	15 mph 25 km/h	20 mph Cyc 30 km/h Cyc	15 mph Cyc 25 km/h Cyc	6 mph Cyc 10 km/h Cyc			Unloaded Dimensions		Loaded Dimensions	
4,080 lbs	4,370 lbs	4,520 lbs	4,650 lbs	4,980 lbs		17 psi	Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	
1,850 kgs	1,980 kgs	2,050 kgs	2,110 kgs	2,260 kgs		1.2 bar	12.4 in	72.7 in	33.9 in	218.1 in	
4,940 lbs	5,290 lbs	5,490 lbs	5,620 lbs	6,020 lbs	6,130 lbs	23 psi	314 mm	1,847 mm	862 mm	5,539 mm	
2,240 kgs	2,400 kgs	2,490 kgs	2,550 kgs	2,730 kgs	2,780 kgs	1.6 bar	Rolling Circumference Index 46				Tube MSPN
5,390 lbs	5,780 lbs	5,990 lbs	6,140 lbs	6,570 lbs	7,200 lbs	29 psi					Number of Lugs 34 x 2
2,445 kgs	2,620 kgs	2,715 kgs	2,785 kgs	2,980 kgs	3,265 kgs	2.0 bar	Gross Flat Plate				Tube CAI
5,840 lbs	6,260 lbs	6,480 lbs	6,660 lbs	7,120 lbs	8,270 lbs	35 psi					Tire Weight
2,650 kgs	2,840 kgs	2,940 kgs	3,020 kgs	3,230 kgs	3,750 kgs	2.4 bar	100% Tire Volume				
6,390 lbs	6,850 lbs	7,100 lbs	7,290 lbs	7,790 lbs	8,930 lbs	41 psi					Centerline Tread Depth
2,900 kgs	3,105 kgs	3,220 kgs	3,305 kgs	3,535 kgs	4,050 kgs	2.8 bar	212 sq in				
6,940 lbs	7,430 lbs	7,720 lbs	7,910 lbs	8,470 lbs	9,590 lbs	46 psi					1,365 sq cm
3,150 kgs	3,370 kgs	3,500 kgs	3,590 kgs	3,840 kgs	4,350 kgs	3.2 bar	Tire Weight				
7,170 lbs	7,660 lbs	7,960 lbs	8,170 lbs	8,740 lbs	10,010 lbs	49 psi					100% Tire Volume
3,250 kgs	3,475 kgs	3,610 kgs	3,705 kgs	3,965 kgs	4,540 kgs	3.4 bar	Centerline Tread Depth				
7,390 lbs	7,890 lbs	8,200 lbs	8,420 lbs	9,020 lbs	10,430 lbs	52 psi					277 sq in
3,350 kgs	3,580 kgs	3,720 kgs	3,820 kgs	4,090 kgs	4,730 kgs	3.6 bar	1,785 sq cm				
					10,760 lbs	55 psi					Tire Weight
					4,880 kgs	3.8 bar	145 kgs				
											439 liters
					11,090 lbs	58 psi	59/32nd				
					5,030 kgs	4.0 bar					47 mm

\*All load values are for maximum indicated speeds at low torque.  
**\*20 mph (30 km/h): high torque field work or max road speed.**  
 \*All load values for ground slopes up to 20% (above 20% consult Michelin)

## 380/90 R50 151A8/151B TL AGRIBIB RC

MSPN: 15852

CAI: 036849

Load per tire (single)							Pressure	Tire Technical Data			
30 mph 50 km/h	20 mph 30 km/h	15 mph 25 km/h	20 mph Cyc 30 km/h Cyc	15 mph Cyc 25 km/h Cyc	6 mph Cyc 10 km/h Cyc			Unloaded Dimensions		Loaded Dimensions	
5,200 lbs	5,570 lbs	5,780 lbs	5,930 lbs	6,350 lbs		17 psi	Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	
2,360 kgs	2,525 kgs	2,620 kgs	2,690 kgs	2,880 kgs		1.2 bar	15.5 in	76.2 in	35.9 in	228.9 in	
5,800 lbs	6,190 lbs	6,440 lbs	6,610 lbs	7,080 lbs		20 psi	393 mm	1,935 mm	912 mm	5,813 mm	
2,630 kgs	2,810 kgs	2,920 kgs	3,000 kgs	3,210 kgs		1.4 bar	Rolling Circumference Index 47				Tube MSPN
6,390 lbs	6,830 lbs	7,100 lbs	7,290 lbs	7,800 lbs	7,800 lbs	23 psi					Number of Lugs 36 x 2
2,900 kgs	3,100 kgs	3,220 kgs	3,305 kgs	3,540 kgs	3,540 kgs	1.6 bar	Gross Flat Plate				Minimum Dual/Triple Spacing
6,700 lbs	7,170 lbs	7,430 lbs	7,630 lbs	8,180 lbs	8,700 lbs	26 psi					Tire Weight
3,040 kgs	3,250 kgs	3,370 kgs	3,460 kgs	3,710 kgs	3,945 kgs	1.8 bar	100% Tire Volume				
7,000 lbs	7,480 lbs	7,770 lbs	7,980 lbs	8,540 lbs	9,590 lbs	29 psi					Centerline Tread Depth
3,175 kgs	3,395 kgs	3,525 kgs	3,620 kgs	3,875 kgs	4,350 kgs	2.0 bar	277 sq in				
7,300 lbs	7,800 lbs	8,110 lbs	8,330 lbs	8,910 lbs	10,040 lbs	32 psi					1,785 sq cm
3,310 kgs	3,540 kgs	3,680 kgs	3,780 kgs	4,040 kgs	4,555 kgs	2.2 bar	Tire Weight				
7,610 lbs	8,140 lbs	8,440 lbs	8,680 lbs	9,280 lbs	10,490 lbs	35 psi					100% Tire Volume
3,450 kgs	3,690 kgs	3,830 kgs	3,935 kgs	4,210 kgs	4,760 kgs	2.4 bar	Centerline Tread Depth				
					10,960 lbs	38 psi					59/32nd
					4,970 kgs	2.6 bar	47 mm				
											145 kgs
					11,180 lbs	39 psi	439 liters				
					5,070 kgs	2.7 bar					519 mm
					11,410 lbs	41 psi					
					5,175 kgs	2.8 bar					

\*All load values are for maximum indicated speeds at low torque.  
**\*20 mph (30 km/h): high torque field work or max road speed.**  
 \*All load values for ground slopes up to 20% (above 20% consult Michelin)

NOTE:

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%





## 320/90 R54 151A8/151B TL AGRIBIB RC

MSPN: 96185

CAI: 272304

Load per tire (single)							Pressure	Tire Technical Data				Rims (preferred in bold) <b>W10</b>							
30 mph 50 km/h	20 mph 30 km/h	15 mph 25 km/h	20 mph Cyc 30 km/h Cyc	15 mph Cyc 25 km/h Cyc	6 mph Cyc 10 km/h Cyc	Unloaded Dimensions		Loaded Dimensions		Rolling Circumference									
4,300 lbs	4,610 lbs	4,760 lbs	4,890 lbs	5,250 lbs		17 psi	Overall Width	Overall Diameter	Loaded Radius		Rolling Circumference	Tube MSPN 97549							
1,950 kgs	2,090 kgs	2,160 kgs	2,220 kgs	2,380 kgs		1.2 bar	12.4	76.8	36	233.5	Tube CAI 170007								
5,200 lbs	5,580 lbs	5,780 lbs	5,930 lbs	6,350 lbs	6,460 lbs	23 psi	315	1950	914	5930		Minimum Dual/Triple Spacing							
2,360 kgs	2,530 kgs	2,620 kgs	2,690 kgs	2,880 kgs	2,930 kgs	1.6 bar	<table border="1"> <tr> <th colspan="2">Rolling Circumference Index</th> </tr> <tr> <td colspan="2">47</td> </tr> <tr> <th colspan="2">Number of Lugs</th> </tr> <tr> <td colspan="2">35</td> </tr> </table>				Rolling Circumference Index		47		Number of Lugs		35		49 psi
Rolling Circumference Index																			
47																			
Number of Lugs																			
35																			
6,010 lbs	6,440 lbs	6,660 lbs	6,860 lbs	7,320 lbs	8,510 lbs	35 psi													
2,725 kgs	2,920 kgs	3,020 kgs	3,110 kgs	3,320 kgs	3,860 kgs	2.4 bar	Gross Flat Plate												
6,590 lbs	7,050 lbs	7,310 lbs	7,520 lbs	8,040 lbs	9,220 lbs	41 psi	Tire Weight												
2,990 kgs	3,200 kgs	3,315 kgs	3,410 kgs	3,645 kgs	4,180 kgs	2.8 bar	100% Tire Volume												
7,170 lbs	7,670 lbs	7,960 lbs	8,180 lbs	8,750 lbs	9,920 lbs	46 psi	Centerline Tread Depth												
3,250 kgs	3,480 kgs	3,610 kgs	3,710 kgs	3,970 kgs	4,500 kgs	3.2 bar	220.1												
7,390 lbs	7,900 lbs	8,200 lbs	8,420 lbs	9,020 lbs	10,340 lbs	49 psi	1420												
3,350 kgs	3,585 kgs	3,720 kgs	3,820 kgs	4,090 kgs	4,690 kgs	3.4 bar	121												
7,610 lbs	8,140 lbs	8,440 lbs	8,660 lbs	9,280 lbs	10,760 lbs	52 psi	84.5												
3,450 kgs	3,690 kgs	3,830 kgs	3,930 kgs	4,210 kgs	4,880 kgs	3.6 bar	49												
					11,090 lbs	55 psi	39												
					5,030 kgs	3.8 bar	434												
					11,420 lbs	58 psi													
					5,180 kgs	4.0 bar													

**NOTE:**

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%

