

MICHELIN BIBSTEEL HARD SURFACE

Radial

Service life



Robustness



Comfort



Sidewall thickness increased by 1/10 in. in comparison to a MICHELIN Stabil'X XZSL tire

Service life with wear and tear on tough surfaces

- Similar tread life of the MICHELIN Stabil'X XZSL tire
- Improved durability of the sidewall

Impact and puncture resistant

- Radial tire with 3 metal plies (1 casing ply and 2 crown plies)
- +1/10 in. sidewall thickness in comparison to a MICHELIN Stabil'X XZSL tire
- Protective trash guard

Successor to the MICHELIN Stabil'X XZSL

- Longer service life due to resistance to wear and tear and punctures
- Less down-time from damages and punctures



Protective trash guard



Skid Steers



Backhoe Loaders



Telehandlers

Sizes

260/70	R16.5 TL 129A8/129B IND	300/70	R16.5 TL 137A8/137B IND
--------	-------------------------	--------	-------------------------

MICHELIN BIBSTEEL HARD SURFACE

Radial

260/70 R16.5 129A8/129B IND TL BIBSTEEL HARD SURFACE

MSPN: 38281

CAI: 275538

Load per tire (single)					Pressure	*All load values are for maximum indicated speeds at low torque. *20 mph (30 km/h): high torque field work or max road speed. *All load values for ground slopes up to 20% (above 20% consult Michelin)																																																																																																																																																																																																																		
30 mph	25 mph	15 mph	Stat	Stat																																																																																																																																																																																																																				
50 km/h	40 km/h	25 km/h	Stat	Pressure	<table border="1"> <thead> <tr> <th colspan="4">Tire Technical Data</th> <th rowspan="2">Rims (preferred in bold)</th> </tr> <tr> <th colspan="2">Unloaded Dimensions</th> <th colspan="2">Loaded Dimensions</th> </tr> <tr> <th>Overall Width</th> <th>Overall Diameter</th> <th>Loaded Radius</th> <th>Rolling Circumference</th> <th rowspan="3">8.25</th> </tr> </thead> <tbody> <tr> <td>10.5 in</td> <td>30.4 in</td> <td>14.0 in</td> <td>90.8 in</td> </tr> <tr> <td>266 mm</td> <td>773 mm</td> <td>355 mm</td> <td>2,307 mm</td> </tr> <tr> <td colspan="4" rowspan="2"> <table border="1"> <tr> <td>Rolling Circumference Index</td> <td>0</td> </tr> <tr> <td>Number of Lugs</td> <td>30 x 2</td> </tr> </table> </td> <td>Tube MSPN</td> </tr> <tr> <td colspan="4" rowspan="2"> <table border="1"> <tr> <td>Gross Flat Plate</td> <td>Tire Weight</td> <td>100% Tire Volume</td> <td>Centerline Tread Depth</td> <td>Minimum Dual/Triple Spacing</td> </tr> <tr> <td>60 sq in</td> <td>73 lbs</td> <td>15.8 gals</td> <td>23/32nd</td> <td>14.3 in</td> </tr> <tr> <td>384 sq cm</td> <td>33 kgs</td> <td>60 liters</td> <td>18 mm</td> <td>363 mm</td> </tr> </table> </td> <td>Tube CAI TL</td> </tr> <tr> <td>1,520 lbs</td> <td>1,520 lbs</td> <td>1,680 lbs</td> <td>3,510 lbs</td> <td>22 psi</td> <td colspan="5" rowspan="20"> <table border="1"> <thead> <tr> <th colspan="4">Tire Technical Data</th> <th rowspan="2">Rims (preferred in bold)</th> </tr> <tr> <th colspan="2">Unloaded Dimensions</th> <th colspan="2">Loaded Dimensions</th> </tr> <tr> <th>Overall Width</th> <th>Overall Diameter</th> <th>Loaded Radius</th> <th>Rolling Circumference</th> <th rowspan="3">9.75</th> </tr> </thead> <tbody> <tr> <td>12.4 in</td> <td>32.7 in</td> <td>14.9 in</td> <td>97.5 in</td> </tr> <tr> <td>315 mm</td> <td>830 mm</td> <td>378 mm</td> <td>2,477 mm</td> </tr> <tr> <td colspan="4" rowspan="2"> <table border="1"> <tr> <td>Rolling Circumference Index</td> <td>0</td> </tr> <tr> <td>Number of Lugs</td> <td>30 x 2</td> </tr> </table> </td> <td>Tube MSPN</td> </tr> <tr> <td colspan="4" rowspan="2"> <table border="1"> <tr> <td>Gross Flat Plate</td> <td>Tire Weight</td> <td>100% Tire Volume</td> <td>Centerline Tread Depth</td> <td>Minimum Dual/Triple Spacing</td> </tr> <tr> <td>73 sq in</td> <td>93 lbs</td> <td>22.7 gals</td> <td>26/32nd</td> <td>16.3 in</td> </tr> <tr> <td>473 sq cm</td> <td>42 kgs</td> <td>86 liters</td> <td>21 mm</td> <td>414 mm</td> </tr> </table> </td> <td>Tube CAI</td> </tr> </tbody> </table> </td> </tr> <tr> <td>690 kgs</td> <td>690 kgs</td> <td>760 kgs</td> <td>1,590 kgs</td> <td>1.5 bar</td> </tr> <tr> <td>1,870 lbs</td> <td>1,870 lbs</td> <td>2,070 lbs</td> <td>4,310 lbs</td> <td>29 psi</td> </tr> <tr> <td>850 kgs</td> <td>850 kgs</td> <td>940 kgs</td> <td>1,955 kgs</td> <td>2.0 bar</td> </tr> <tr> <td>2,170 lbs</td> <td>2,170 lbs</td> <td>2,400 lbs</td> <td>4,980 lbs</td> <td>35 psi</td> </tr> <tr> <td>985 kgs</td> <td>985 kgs</td> <td>1,090 kgs</td> <td>2,260 kgs</td> <td>2.4 bar</td> </tr> <tr> <td>2,460 lbs</td> <td>2,460 lbs</td> <td>2,730 lbs</td> <td>5,650 lbs</td> <td>41 psi</td> </tr> <tr> <td>1,115 kgs</td> <td>1,115 kgs</td> <td>1,240 kgs</td> <td>2,565 kgs</td> <td>2.8 bar</td> </tr> <tr> <td>2,760 lbs</td> <td>2,760 lbs</td> <td>3,060 lbs</td> <td>6,330 lbs</td> <td>46 psi</td> </tr> <tr> <td>1,250 kgs</td> <td>1,250 kgs</td> <td>1,390 kgs</td> <td>2,870 kgs</td> <td>3.2 bar</td> </tr> <tr> <td>3,050 lbs</td> <td>3,050 lbs</td> <td>3,400 lbs</td> <td>7,010 lbs</td> <td>52 psi</td> </tr> <tr> <td>1,385 kgs</td> <td>1,385 kgs</td> <td>1,540 kgs</td> <td>3,180 kgs</td> <td>3.6 bar</td> </tr> <tr> <td>3,340 lbs</td> <td>3,340 lbs</td> <td>3,710 lbs</td> <td>7,680 lbs</td> <td>58 psi</td> </tr> <tr> <td>1,515 kgs</td> <td>1,515 kgs</td> <td>1,685 kgs</td> <td>3,485 kgs</td> <td>4.0 bar</td> </tr> <tr> <td>3,640 lbs</td> <td>3,640 lbs</td> <td>4,050 lbs</td> <td>8,370 lbs</td> <td>64 psi</td> </tr> <tr> <td>1,650 kgs</td> <td>1,650 kgs</td> <td>1,835 kgs</td> <td>3,795 kgs</td> <td>4.4 bar</td> </tr> <tr> <td>3,940 lbs</td> <td>3,940 lbs</td> <td>4,370 lbs</td> <td>9,040 lbs</td> <td>70 psi</td> </tr> <tr> <td>1,785 kgs</td> <td>1,785 kgs</td> <td>1,980 kgs</td> <td>4,100 kgs</td> <td>4.8 bar</td> </tr> <tr> <td>4,080 lbs</td> <td>4,080 lbs</td> <td>4,530 lbs</td> <td>9,380 lbs</td> <td>73 psi</td> </tr> <tr> <td>1,850 kgs</td> <td>1,850 kgs</td> <td>2,055 kgs</td> <td>4,255 kgs</td> <td>5.0 bar</td> </tr> </tbody> </table>					Tire Technical Data				Rims (preferred in bold)	Unloaded Dimensions		Loaded Dimensions		Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	8.25	10.5 in	30.4 in	14.0 in	90.8 in	266 mm	773 mm	355 mm	2,307 mm	<table border="1"> <tr> <td>Rolling Circumference Index</td> <td>0</td> </tr> <tr> <td>Number of Lugs</td> <td>30 x 2</td> </tr> </table>				Rolling Circumference Index	0	Number of Lugs	30 x 2	Tube MSPN	<table border="1"> <tr> <td>Gross Flat Plate</td> <td>Tire Weight</td> <td>100% Tire Volume</td> <td>Centerline Tread Depth</td> <td>Minimum Dual/Triple Spacing</td> </tr> <tr> <td>60 sq in</td> <td>73 lbs</td> <td>15.8 gals</td> <td>23/32nd</td> <td>14.3 in</td> </tr> <tr> <td>384 sq cm</td> <td>33 kgs</td> <td>60 liters</td> <td>18 mm</td> <td>363 mm</td> </tr> </table>				Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing	60 sq in	73 lbs	15.8 gals	23/32nd	14.3 in	384 sq cm	33 kgs	60 liters	18 mm	363 mm	Tube CAI TL	1,520 lbs	1,520 lbs	1,680 lbs	3,510 lbs	22 psi	<table border="1"> <thead> <tr> <th colspan="4">Tire Technical Data</th> <th rowspan="2">Rims (preferred in bold)</th> </tr> <tr> <th colspan="2">Unloaded Dimensions</th> <th colspan="2">Loaded Dimensions</th> </tr> <tr> <th>Overall Width</th> <th>Overall Diameter</th> <th>Loaded Radius</th> <th>Rolling Circumference</th> <th rowspan="3">9.75</th> </tr> </thead> <tbody> <tr> <td>12.4 in</td> <td>32.7 in</td> <td>14.9 in</td> <td>97.5 in</td> </tr> <tr> <td>315 mm</td> <td>830 mm</td> <td>378 mm</td> <td>2,477 mm</td> </tr> <tr> <td colspan="4" rowspan="2"> <table border="1"> <tr> <td>Rolling Circumference Index</td> <td>0</td> </tr> <tr> <td>Number of Lugs</td> <td>30 x 2</td> </tr> </table> </td> <td>Tube MSPN</td> </tr> <tr> <td colspan="4" rowspan="2"> <table border="1"> <tr> <td>Gross Flat Plate</td> <td>Tire Weight</td> <td>100% Tire Volume</td> <td>Centerline Tread Depth</td> <td>Minimum Dual/Triple Spacing</td> </tr> <tr> <td>73 sq in</td> <td>93 lbs</td> <td>22.7 gals</td> <td>26/32nd</td> <td>16.3 in</td> </tr> <tr> <td>473 sq cm</td> <td>42 kgs</td> <td>86 liters</td> <td>21 mm</td> <td>414 mm</td> </tr> </table> </td> <td>Tube CAI</td> </tr> </tbody> </table>					Tire Technical Data				Rims (preferred in bold)	Unloaded Dimensions		Loaded Dimensions		Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	9.75	12.4 in	32.7 in	14.9 in	97.5 in	315 mm	830 mm	378 mm	2,477 mm	<table border="1"> <tr> <td>Rolling Circumference Index</td> <td>0</td> </tr> <tr> <td>Number of Lugs</td> <td>30 x 2</td> </tr> </table>				Rolling Circumference Index	0	Number of Lugs	30 x 2	Tube MSPN	<table border="1"> <tr> <td>Gross Flat Plate</td> <td>Tire Weight</td> <td>100% Tire Volume</td> <td>Centerline Tread Depth</td> <td>Minimum Dual/Triple Spacing</td> </tr> <tr> <td>73 sq in</td> <td>93 lbs</td> <td>22.7 gals</td> <td>26/32nd</td> <td>16.3 in</td> </tr> <tr> <td>473 sq cm</td> <td>42 kgs</td> <td>86 liters</td> <td>21 mm</td> <td>414 mm</td> </tr> </table>				Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing	73 sq in	93 lbs	22.7 gals	26/32nd	16.3 in	473 sq cm	42 kgs	86 liters	21 mm	414 mm	Tube CAI	690 kgs	690 kgs	760 kgs	1,590 kgs	1.5 bar	1,870 lbs	1,870 lbs	2,070 lbs	4,310 lbs	29 psi	850 kgs	850 kgs	940 kgs	1,955 kgs	2.0 bar	2,170 lbs	2,170 lbs	2,400 lbs	4,980 lbs	35 psi	985 kgs	985 kgs	1,090 kgs	2,260 kgs	2.4 bar	2,460 lbs	2,460 lbs	2,730 lbs	5,650 lbs	41 psi	1,115 kgs	1,115 kgs	1,240 kgs	2,565 kgs	2.8 bar	2,760 lbs	2,760 lbs	3,060 lbs	6,330 lbs	46 psi	1,250 kgs	1,250 kgs	1,390 kgs	2,870 kgs	3.2 bar	3,050 lbs	3,050 lbs	3,400 lbs	7,010 lbs	52 psi	1,385 kgs	1,385 kgs	1,540 kgs	3,180 kgs	3.6 bar	3,340 lbs	3,340 lbs	3,710 lbs	7,680 lbs	58 psi	1,515 kgs	1,515 kgs	1,685 kgs	3,485 kgs	4.0 bar	3,640 lbs	3,640 lbs	4,050 lbs	8,370 lbs	64 psi	1,650 kgs	1,650 kgs	1,835 kgs	3,795 kgs	4.4 bar	3,940 lbs	3,940 lbs	4,370 lbs	9,040 lbs	70 psi	1,785 kgs	1,785 kgs	1,980 kgs	4,100 kgs	4.8 bar	4,080 lbs	4,080 lbs	4,530 lbs	9,380 lbs	73 psi	1,850 kgs	1,850 kgs	2,055 kgs	4,255 kgs	5.0 bar
Tire Technical Data				Rims (preferred in bold)																																																																																																																																																																																																																				
Unloaded Dimensions		Loaded Dimensions																																																																																																																																																																																																																						
Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	8.25																																																																																																																																																																																																																				
10.5 in	30.4 in	14.0 in	90.8 in																																																																																																																																																																																																																					
266 mm	773 mm	355 mm	2,307 mm																																																																																																																																																																																																																					
<table border="1"> <tr> <td>Rolling Circumference Index</td> <td>0</td> </tr> <tr> <td>Number of Lugs</td> <td>30 x 2</td> </tr> </table>				Rolling Circumference Index						0	Number of Lugs	30 x 2	Tube MSPN																																																																																																																																																																																																											
				Rolling Circumference Index						0																																																																																																																																																																																																														
Number of Lugs	30 x 2																																																																																																																																																																																																																							
<table border="1"> <tr> <td>Gross Flat Plate</td> <td>Tire Weight</td> <td>100% Tire Volume</td> <td>Centerline Tread Depth</td> <td>Minimum Dual/Triple Spacing</td> </tr> <tr> <td>60 sq in</td> <td>73 lbs</td> <td>15.8 gals</td> <td>23/32nd</td> <td>14.3 in</td> </tr> <tr> <td>384 sq cm</td> <td>33 kgs</td> <td>60 liters</td> <td>18 mm</td> <td>363 mm</td> </tr> </table>				Gross Flat Plate						Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing	60 sq in	73 lbs	15.8 gals	23/32nd	14.3 in	384 sq cm	33 kgs	60 liters	18 mm	363 mm	Tube CAI TL																																																																																																																																																																																																
				Gross Flat Plate						Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing																																																																																																																																																																																																											
60 sq in	73 lbs	15.8 gals	23/32nd	14.3 in																																																																																																																																																																																																																				
384 sq cm	33 kgs	60 liters	18 mm	363 mm																																																																																																																																																																																																																				
1,520 lbs	1,520 lbs	1,680 lbs	3,510 lbs	22 psi						<table border="1"> <thead> <tr> <th colspan="4">Tire Technical Data</th> <th rowspan="2">Rims (preferred in bold)</th> </tr> <tr> <th colspan="2">Unloaded Dimensions</th> <th colspan="2">Loaded Dimensions</th> </tr> <tr> <th>Overall Width</th> <th>Overall Diameter</th> <th>Loaded Radius</th> <th>Rolling Circumference</th> <th rowspan="3">9.75</th> </tr> </thead> <tbody> <tr> <td>12.4 in</td> <td>32.7 in</td> <td>14.9 in</td> <td>97.5 in</td> </tr> <tr> <td>315 mm</td> <td>830 mm</td> <td>378 mm</td> <td>2,477 mm</td> </tr> <tr> <td colspan="4" rowspan="2"> <table border="1"> <tr> <td>Rolling Circumference Index</td> <td>0</td> </tr> <tr> <td>Number of Lugs</td> <td>30 x 2</td> </tr> </table> </td> <td>Tube MSPN</td> </tr> <tr> <td colspan="4" rowspan="2"> <table border="1"> <tr> <td>Gross Flat Plate</td> <td>Tire Weight</td> <td>100% Tire Volume</td> <td>Centerline Tread Depth</td> <td>Minimum Dual/Triple Spacing</td> </tr> <tr> <td>73 sq in</td> <td>93 lbs</td> <td>22.7 gals</td> <td>26/32nd</td> <td>16.3 in</td> </tr> <tr> <td>473 sq cm</td> <td>42 kgs</td> <td>86 liters</td> <td>21 mm</td> <td>414 mm</td> </tr> </table> </td> <td>Tube CAI</td> </tr> </tbody> </table>					Tire Technical Data				Rims (preferred in bold)	Unloaded Dimensions		Loaded Dimensions		Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	9.75	12.4 in	32.7 in	14.9 in	97.5 in	315 mm	830 mm	378 mm	2,477 mm	<table border="1"> <tr> <td>Rolling Circumference Index</td> <td>0</td> </tr> <tr> <td>Number of Lugs</td> <td>30 x 2</td> </tr> </table>				Rolling Circumference Index	0	Number of Lugs	30 x 2	Tube MSPN	<table border="1"> <tr> <td>Gross Flat Plate</td> <td>Tire Weight</td> <td>100% Tire Volume</td> <td>Centerline Tread Depth</td> <td>Minimum Dual/Triple Spacing</td> </tr> <tr> <td>73 sq in</td> <td>93 lbs</td> <td>22.7 gals</td> <td>26/32nd</td> <td>16.3 in</td> </tr> <tr> <td>473 sq cm</td> <td>42 kgs</td> <td>86 liters</td> <td>21 mm</td> <td>414 mm</td> </tr> </table>				Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing	73 sq in	93 lbs	22.7 gals	26/32nd	16.3 in	473 sq cm	42 kgs	86 liters	21 mm	414 mm	Tube CAI																																																																																																																																																							
Tire Technical Data				Rims (preferred in bold)																																																																																																																																																																																																																				
Unloaded Dimensions		Loaded Dimensions																																																																																																																																																																																																																						
Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	9.75																																																																																																																																																																																																																				
12.4 in	32.7 in	14.9 in	97.5 in																																																																																																																																																																																																																					
315 mm	830 mm	378 mm	2,477 mm																																																																																																																																																																																																																					
<table border="1"> <tr> <td>Rolling Circumference Index</td> <td>0</td> </tr> <tr> <td>Number of Lugs</td> <td>30 x 2</td> </tr> </table>				Rolling Circumference Index											0	Number of Lugs	30 x 2	Tube MSPN																																																																																																																																																																																																						
				Rolling Circumference Index	0																																																																																																																																																																																																																			
Number of Lugs	30 x 2																																																																																																																																																																																																																							
<table border="1"> <tr> <td>Gross Flat Plate</td> <td>Tire Weight</td> <td>100% Tire Volume</td> <td>Centerline Tread Depth</td> <td>Minimum Dual/Triple Spacing</td> </tr> <tr> <td>73 sq in</td> <td>93 lbs</td> <td>22.7 gals</td> <td>26/32nd</td> <td>16.3 in</td> </tr> <tr> <td>473 sq cm</td> <td>42 kgs</td> <td>86 liters</td> <td>21 mm</td> <td>414 mm</td> </tr> </table>				Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing	73 sq in						93 lbs	22.7 gals	26/32nd	16.3 in	473 sq cm	42 kgs	86 liters	21 mm	414 mm	Tube CAI																																																																																																																																																																																																
				Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing																																																																																																																																																																																																																
73 sq in	93 lbs	22.7 gals	26/32nd	16.3 in																																																																																																																																																																																																																				
473 sq cm	42 kgs	86 liters	21 mm	414 mm																																																																																																																																																																																																																				
690 kgs	690 kgs	760 kgs	1,590 kgs	1.5 bar																																																																																																																																																																																																																				
1,870 lbs	1,870 lbs	2,070 lbs	4,310 lbs	29 psi																																																																																																																																																																																																																				
850 kgs	850 kgs	940 kgs	1,955 kgs	2.0 bar																																																																																																																																																																																																																				
2,170 lbs	2,170 lbs	2,400 lbs	4,980 lbs	35 psi																																																																																																																																																																																																																				
985 kgs	985 kgs	1,090 kgs	2,260 kgs	2.4 bar																																																																																																																																																																																																																				
2,460 lbs	2,460 lbs	2,730 lbs	5,650 lbs	41 psi																																																																																																																																																																																																																				
1,115 kgs	1,115 kgs	1,240 kgs	2,565 kgs	2.8 bar																																																																																																																																																																																																																				
2,760 lbs	2,760 lbs	3,060 lbs	6,330 lbs	46 psi																																																																																																																																																																																																																				
1,250 kgs	1,250 kgs	1,390 kgs	2,870 kgs	3.2 bar																																																																																																																																																																																																																				
3,050 lbs	3,050 lbs	3,400 lbs	7,010 lbs	52 psi																																																																																																																																																																																																																				
1,385 kgs	1,385 kgs	1,540 kgs	3,180 kgs	3.6 bar																																																																																																																																																																																																																				
3,340 lbs	3,340 lbs	3,710 lbs	7,680 lbs	58 psi																																																																																																																																																																																																																				
1,515 kgs	1,515 kgs	1,685 kgs	3,485 kgs	4.0 bar																																																																																																																																																																																																																				
3,640 lbs	3,640 lbs	4,050 lbs	8,370 lbs	64 psi																																																																																																																																																																																																																				
1,650 kgs	1,650 kgs	1,835 kgs	3,795 kgs	4.4 bar																																																																																																																																																																																																																				
3,940 lbs	3,940 lbs	4,370 lbs	9,040 lbs	70 psi																																																																																																																																																																																																																				
1,785 kgs	1,785 kgs	1,980 kgs	4,100 kgs	4.8 bar																																																																																																																																																																																																																				
4,080 lbs	4,080 lbs	4,530 lbs	9,380 lbs	73 psi																																																																																																																																																																																																																				
1,850 kgs	1,850 kgs	2,055 kgs	4,255 kgs	5.0 bar																																																																																																																																																																																																																				

300/70 R16.5 137A8/137B IND TL BIBSTEEL HARD SURFACE

MSPN: 84590

CAI: 241265

Load per tire (single)					Pressure	*All load values are for maximum indicated speeds at low torque. *20 mph (30 km/h): high torque field work or max road speed. *All load values for ground slopes up to 20% (above 20% consult Michelin)																																																						
30 mph	25 mph	15 mph	Stat	Stat																																																								
50 km/h	40 km/h	25 km/h	Stat	Pressure	<table border="1"> <thead> <tr> <th colspan="4">Tire Technical Data</th> <th rowspan="2">Rims (preferred in bold)</th> </tr> <tr> <th colspan="2">Unloaded Dimensions</th> <th colspan="2">Loaded Dimensions</th> </tr> <tr> <th>Overall Width</th> <th>Overall Diameter</th> <th>Loaded Radius</th> <th>Rolling Circumference</th> <th rowspan="3">9.75</th> </tr> </thead> <tbody> <tr> <td>12.4 in</td> <td>32.7 in</td> <td>14.9 in</td> <td>97.5 in</td> </tr> <tr> <td>315 mm</td> <td>830 mm</td> <td>378 mm</td> <td>2,477 mm</td> </tr> <tr> <td colspan="4" rowspan="2"> <table border="1"> <tr> <td>Rolling Circumference Index</td> <td>0</td> </tr> <tr> <td>Number of Lugs</td> <td>30 x 2</td> </tr> </table> </td> <td>Tube MSPN</td> </tr> <tr> <td colspan="4" rowspan="2"> <table border="1"> <tr> <td>Gross Flat Plate</td> <td>Tire Weight</td> <td>100% Tire Volume</td> <td>Centerline Tread Depth</td> <td>Minimum Dual/Triple Spacing</td> </tr> <tr> <td>73 sq in</td> <td>93 lbs</td> <td>22.7 gals</td> <td>26/32nd</td> <td>16.3 in</td> </tr> <tr> <td>473 sq cm</td> <td>42 kgs</td> <td>86 liters</td> <td>21 mm</td> <td>414 mm</td> </tr> </table> </td> <td>Tube CAI</td> </tr> </tbody> </table>					Tire Technical Data				Rims (preferred in bold)	Unloaded Dimensions		Loaded Dimensions		Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	9.75	12.4 in	32.7 in	14.9 in	97.5 in	315 mm	830 mm	378 mm	2,477 mm	<table border="1"> <tr> <td>Rolling Circumference Index</td> <td>0</td> </tr> <tr> <td>Number of Lugs</td> <td>30 x 2</td> </tr> </table>				Rolling Circumference Index	0	Number of Lugs	30 x 2	Tube MSPN	<table border="1"> <tr> <td>Gross Flat Plate</td> <td>Tire Weight</td> <td>100% Tire Volume</td> <td>Centerline Tread Depth</td> <td>Minimum Dual/Triple Spacing</td> </tr> <tr> <td>73 sq in</td> <td>93 lbs</td> <td>22.7 gals</td> <td>26/32nd</td> <td>16.3 in</td> </tr> <tr> <td>473 sq cm</td> <td>42 kgs</td> <td>86 liters</td> <td>21 mm</td> <td>414 mm</td> </tr> </table>				Gross Flat Plate	Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing	73 sq in	93 lbs	22.7 gals	26/32nd	16.3 in	473 sq cm	42 kgs	86 liters	21 mm	414 mm	Tube CAI
Tire Technical Data				Rims (preferred in bold)																																																								
Unloaded Dimensions		Loaded Dimensions																																																										
Overall Width	Overall Diameter	Loaded Radius	Rolling Circumference	9.75																																																								
12.4 in	32.7 in	14.9 in	97.5 in																																																									
315 mm	830 mm	378 mm	2,477 mm																																																									
<table border="1"> <tr> <td>Rolling Circumference Index</td> <td>0</td> </tr> <tr> <td>Number of Lugs</td> <td>30 x 2</td> </tr> </table>				Rolling Circumference Index						0	Number of Lugs	30 x 2	Tube MSPN																																															
				Rolling Circumference Index						0																																																		
Number of Lugs	30 x 2																																																											
<table border="1"> <tr> <td>Gross Flat Plate</td> <td>Tire Weight</td> <td>100% Tire Volume</td> <td>Centerline Tread Depth</td> <td>Minimum Dual/Triple Spacing</td> </tr> <tr> <td>73 sq in</td> <td>93 lbs</td> <td>22.7 gals</td> <td>26/32nd</td> <td>16.3 in</td> </tr> <tr> <td>473 sq cm</td> <td>42 kgs</td> <td>86 liters</td> <td>21 mm</td> <td>414 mm</td> </tr> </table>				Gross Flat Plate						Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing	73 sq in	93 lbs	22.7 gals	26/32nd	16.3 in	473 sq cm	42 kgs	86 liters	21 mm	414 mm	Tube CAI																																				
				Gross Flat Plate						Tire Weight	100% Tire Volume	Centerline Tread Depth	Minimum Dual/Triple Spacing																																															
73 sq in	93 lbs	22.7 gals	26/32nd	16.3 in																																																								
473 sq cm	42 kgs	86 liters	21 mm	414 mm																																																								
1,930 lbs	1,930 lbs	2,140 lbs	4,430 lbs	22 psi																																																								
875 kgs	875 kgs	970 kgs	2,010 kgs	1.5 bar																																																								
2,340 lbs	2,340 lbs	2,600 lbs	5,380 lbs	29 psi																																																								
1,060 kgs	1,060 kgs	1,180 kgs	2,440 kgs	2.0 bar																																																								
2,700 lbs	2,700 lbs	3,000 lbs	6,210 lbs	35 psi																																																								
1,225 kgs	1,225 kgs	1,360 kgs	2,815 kgs	2.4 bar																																																								
3,050 lbs	3,050 lbs	3,400 lbs	7,030 lbs	41 psi																																																								
1,385 kgs	1,385 kgs	1,540 kgs	3,190 kgs	2.8 bar																																																								
3,420 lbs	3,420 lbs	3,790 lbs	7,860 lbs	46 psi																																																								
1,550 kgs	1,550 kgs	1,720 kgs	3,565 kgs	3.2 bar																																																								
3,780 lbs	3,780 lbs	4,200 lbs	8,710 lbs	52 psi																																																								
1,715 kgs	1,715 kgs	1,905 kgs	3,950 kgs	3.6 bar																																																								
4,160 lbs	4,160 lbs	4,610 lbs	9,550 lbs	58 psi																																																								
1,885 kgs	1,885 kgs	2,090 kgs	4,330 kgs	4.0 bar																																																								
4,520 lbs	4,520 lbs	5,020 lbs	10,390 lbs	64 psi																																																								
2,050 kgs	2,050 kgs	2,275 kgs	4,715 kgs	4.4 bar																																																								
4,880 lbs	4,880 lbs	5,420 lbs	11,240 lbs	70 psi																																																								
2,215 kgs	2,215 kgs	2,460 kgs	5,100 kgs	4.8 bar																																																								
5,070 lbs	5,070 lbs	5,620 lbs	11,660 lbs	73 psi																																																								
2,300 kgs	2,300 kgs	2,550 kgs	5,290 kgs	5.0 bar																																																								

NOTE:

- When used as duals, tire load carrying capacity must be reduced 12%
- When used as triples, tire load carrying capacity must be reduced 18%

